SAFETY DATA SHEET

Cellulose Thinners

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

▼Trade name

Cellulose Thinners

1.2. Relevant identified uses of the substance or mixture and uses advised against

▼Relevant identified uses of the substance or mixture

Thinner

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

John Myland Ltd.
26 Rothschild St,
Norwood
SE27 0HQ London
England
Tel: +44 (0) 208 670 9161
mylands.com

Contact person

Mylands

▼E-mail

info@mylands.com

Revision

10/09/2025

SDS Version

3.0

Date of previous version

25/07/2024 (2.0)

1.4. ▼Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.


2.1. ▼Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.
STOT SE 3; H336, May cause drowsiness or dizziness.
Repr. 2; H361, Suspected of damaging fertility or the unborn child.
STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

▼Hazard statement(s)

Highly flammable liquid and vapour. (H225)
May be fatal if swallowed and enters airways. (H304)
Causes skin irritation. (H315)
Causes serious eye damage. (H318)
May cause drowsiness or dizziness. (H336)
Suspected of damaging fertility or the unborn child. (H361)
May cause damage to organs through prolonged or repeated exposure. (H373)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Do not breathe vapour/mist. (P260)
Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
Get medical advice/attention if you feel unwell. (P314)

Storage

Store locked up. (P405)

▼Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

toluene
propan-2-ol;isopropyl alcohol;isopropanol
n-butyl acetate
2-methylpropan-1-ol;iso-butanol

▼Additional labelling

2.3. Other hazards

▼Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
toluene	CAS No.: 108-88-3 EC No.: 203-625-9 UK-REACH: Index No.: 601-021-00-3	40-60%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361 STOT RE 2, H373 Aquatic Chronic 3, H412	[1], [3]
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	15-25%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
n-butyl acetate	CAS No.: 123-86-4 EC No.: 204-658-1 UK-REACH: Index No.: 607-025-00-1	10-15%	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336	[1]
2-methylpropan-1-ol;iso-butanol	CAS No.: 78-83-1 EC No.: 201-148-0 UK-REACH: Index No.: 603-108-00-1	5-10%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	
p-xylene;m-xylene;xylene;o-xylene	CAS No.: 1330-20-7 EC No.: 215-535-7 UK-REACH: Index No.: 601-022-00-9	5-10%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	[1]
acetone;propan-2-one;propanone	CAS No.: 67-64-1 EC No.: 200-662-2 UK-REACH: Index No.: 606-001-00-8	5-10%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
4-hydroxy-4-methylpentan-2-one;diacetone alcohol	CAS No.: 123-42-2 EC No.: 204-626-7 UK-REACH: Index No.: 603-016-00-1	1-3%	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.
[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.
The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)

5.3. ▼Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: ●3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼Precautions for safe handling

Ground and bond container and receiving equipment.
Use explosion-proof [electrical/lighting/ventilating] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.
Avoid direct contact with the product.
Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap.
Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:
1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Take action to prevent static discharges.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

▼Storage conditions

No specific requirements.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼Control parameters

toluene
Long term exposure limit (8 hours) (ppm): 50
Long term exposure limit (8 hours) (mg/m³): 191
Short term exposure limit (15 minutes) (ppm): 100
Short term exposure limit (15 minutes) (mg/m³): 384
Annotations:
Sk = Can be absorbed through the skin and lead to systemic toxicity.

propan-2-ol;isopropyl alcohol;isopropanol
Long term exposure limit (8 hours) (ppm): 400
Long term exposure limit (8 hours) (mg/m³): 999
Short term exposure limit (15 minutes) (ppm): 500
Short term exposure limit (15 minutes) (mg/m³): 1250

n-butyl acetate
Long term exposure limit (8 hours) (ppm): 150
Long term exposure limit (8 hours) (mg/m³): 724
Short term exposure limit (15 minutes) (ppm): 200
Short term exposure limit (15 minutes) (mg/m³): 966

2-methylpropan-1-ol;iso-butanol
Long term exposure limit (8 hours) (ppm): 50
Long term exposure limit (8 hours) (mg/m³): 154
Short term exposure limit (15 minutes) (ppm): 75
Short term exposure limit (15 minutes) (mg/m³): 231

p-xylene;m-xylene;xylene;o-xylene
Long term exposure limit (8 hours) (ppm): 50
Long term exposure limit (8 hours) (mg/m³): 220
Short term exposure limit (15 minutes) (ppm): 100
Short term exposure limit (15 minutes) (mg/m³): 441
Annotations:
BMVG = Biological Monitoring Guidance Value exists
Sk = Can be absorbed through the skin and lead to systemic toxicity.

acetone;propan-2-one;propanone
Long term exposure limit (8 hours) (ppm): 500
Long term exposure limit (8 hours) (mg/m³): 1210
Short term exposure limit (15 minutes) (ppm): 1500
Short term exposure limit (15 minutes) (mg/m³): 3620

4-hydroxy-4-methylpentan-2-one;diacetone alcohol
Long term exposure limit (8 hours) (ppm): 50
Long term exposure limit (8 hours) (mg/m³): 241
Short term exposure limit (15 minutes) (ppm): 75
Short term exposure limit (15 minutes) (mg/m³): 362

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼DNEL

2-methylpropan-1-ol;iso-butanol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	55 mg/m³
Long term – Local effects - Workers	Inhalation	310 mg/m³

4-hydroxy-4-methylpentan-2-one;diacetone alcohol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	33 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	467 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	5.8 mg/m³
Long term – Systemic effects - Workers	Inhalation	32.6 mg/m³
Short term – Local effects - Workers	Inhalation	240 mg/m³
Long term – Systemic effects - General population	Oral	1.67 mg/kg bw/day

acetone;propan-2-one;propanone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	186 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	200 mg/m³
Long term – Systemic effects - Workers	Inhalation	1210 mg/m³
Short term – Local effects - Workers	Inhalation	2420 mg/m³
Long term – Systemic effects - General population	Oral	62 mg/kg bw/day

p-xylene;m-xylene;xylene;o-xylene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	125 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	212 mg/kg bw/day
Long term – Local effects - General population	Inhalation	65.3 mg/m³
Long term – Local effects - Workers	Inhalation	221 mg/m³
Long term – Systemic effects - General population	Inhalation	65.3 mg/m³
Long term – Systemic effects - Workers	Inhalation	221 mg/m³
Short term – Local effects - General population	Inhalation	260 mg/m³
Short term – Local effects - Workers	Inhalation	442 mg/m³
Short term – Systemic effects - General population	Inhalation	260 mg/m³
Short term – Systemic effects - Workers	Inhalation	442 mg/m³
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m³
Long term – Systemic effects - Workers	Inhalation	500 mg/m³

Short term – Systemic effects - General population	Inhalation	178 mg/m³
Short term – Systemic effects - Workers	Inhalation	1000 mg/m³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

toluene

Duration:	**Route of exposure:**	**DNEL:**
Long term – Systemic effects - General population	Dermal	226 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	384 mg/kg bw/day
Long term – Local effects - General population	Inhalation	56.5 mg/m³
Long term – Local effects - Workers	Inhalation	192 mg/m³
Long term – Systemic effects - General population	Inhalation	56.5 mg/m³
Long term – Systemic effects - Workers	Inhalation	192 mg/m³
Short term – Local effects - General population	Inhalation	226 mg/m³
Short term – Local effects - Workers	Inhalation	384 mg/m³
Short term – Systemic effects - General population	Inhalation	226 mg/m³
Short term – Systemic effects - Workers	Inhalation	384 mg/m³
Long term – Systemic effects - General population	Oral	8.13 mg/kg bw/day

▼ PNEC

2-methylpropan-1-ol;iso-butanol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		400 µg/L
Freshwater sediment		1.56 mg/kg
Intermittent release (freshwater)		11 mg/L
Marine water		40 µg/L
Marine water sediment		156 µg/kg
Sewage treatment plant		10 mg/L
Soil		76.5 µg/kg

4-hydroxy-4-methylpentan-2-one;diacetone alcohol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		2 mg/L
Freshwater sediment		7.4 mg/kg
Intermittent release (freshwater)		1 mg/L
Marine water		200 µg/L
Marine water sediment		740 µg/kg
Sewage treatment plant		100 mg/L
Soil		300 µg/kg

acetone;propan-2-one;propanone

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		10.6 mg/L
Freshwater sediment		30.4 mg/kg
Intermittent release (freshwater)		21 mg/L

Marine water		1.06 mg/L
Marine water sediment		3.04 mg/kg
Sewage treatment plant		100 mg/L
Soil		29.5 mg/kg

p-xylene;m-xylene;xylene;o-xylene

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		44-327 µg/L
Freshwater sediment		2.52-12.46 mg/kg
Intermittent release (freshwater)		10-327 µg/L
Intermittent release (marine water)		1 µg/L
Marine water		4.4-327 µg/L
Marine water sediment		252-12460 µg/kg
Sewage treatment plant		1.6-6.58 mg/L
Soil		852-2310 µg/kg

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

toluene

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		74-680 µg/L
Freshwater sediment		1.78-16.39 mg/kg
Intermittent release (freshwater)		37.8-680 µg/L
Intermittent release (marine water)		3.78 µg/L
Marine water		7.4-680 µg/L
Marine water sediment		178-16390 µg/kg
Sewage treatment plant		840-13610 µg/L
Soil		313-2890 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Do not recirculate outlet air that contain the substances.
The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.
Ensure that eyewash stations and safety showers are located within easy reach.
Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

▼Respiratory Equipment

Type	Class	Colour	Standards
Respirator with the following filter:	Organic vapour filter	Organic vapour filter	EN14387

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

▼Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,5	> 480	EN374-2, EN16523-13, EN388	

▼Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

▼Colour

Colourless

▼Odour / Odour threshold

Perceptible odour

▼pH

No data available.

▼Density (g/cm^3)

No data available.

▼Kinematic viscosity
No data available.

Particle characteristics
Does not apply to liquids.

Phase changes

▼Melting point/Freezing point (°C)
No data available.

Softening point/range (°C)
Does not apply to liquids.

▼Boiling point (°C)
55

▼Vapour pressure
24.7 kPa

▼Relative vapour density
No data available.

▼Decomposition temperature (°C)
No data available.

Data on fire and explosion hazards

▼Flash point (°C)
4

Flammability (°C)
The material is ignitable.

▼Auto-ignition temperature (°C)
No data available.

▼Lower and upper explosion limit (% v/v)
No data available.

Solubility

▼Solubility in water
No data available.

▼n-octanol/water coefficient (LogKow)
No data available.

▼Solubility in fat (g/L)
No data available.

9.2. Other information

▼Oxidizing properties
No data available.

Other physical and chemical parameters
No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.

10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions
None known.

10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

▼Acute toxicity

Based on available data for the mixture, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

▼Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

▼Skin sensitisation

Based on available data for the mixture, the classification criteria are not met.

▼Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

▼Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

Reproductive toxicity: This product contains teratogenic substances, which may produce anomalies and/or developmental defects to the human offspring. Adverse effects include: death, growth retardation, congenital disorders, delayed mental development, and functional disorders. This product contains reprotoxic substances, which may harm the reproductive capacity. Adverse effects include: sterility, effects on the sexual function, lowered effective fertility and dysfunctional menstrual cycle.

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

toluene has been classified by IARC as a group 3 carcinogen.

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. ▼Toxicity
Harmful to aquatic life with long lasting effects.

12.2. ▼Persistence and degradability
Based on available data for the mixture, the classification criteria are not met.

12.3. ▼Bioaccumulative potential
Based on available data for the mixture, the classification criteria are not met.

12.4. Mobility in soil
No data available.

12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties
This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. ▼Other adverse effects
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

▼Waste treatment methods
Product is covered by the regulations on hazardous waste.
HP 3 - Flammable
HP 4 - Irritant (skin irritation and eye damage)
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 10 – Toxic for reproduction
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code
Not applicable.

Specific labelling

Contaminated packing
Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	Limited quantities: 5 L EmS: F-E S-E

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
						See below for additional information.
IATA	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group
** Environmental hazards

▼Additional information

This product is within scope of the regulations of transport of dangerous goods.
ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
Hazchem Code: ●3YE

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

Regulation on drug precursors

toluene is included (Category 3)
acetone;propan-2-one;propanone is included (Category 3)

Regulation on explosives precursors

acetone;propan-2-one;propanone (Annex II)

UK-REACH, Annex XVII

toluene is subject to restrictions, UK-REACH annex XVII (entry 48).
toluene is subject to UK-REACH restrictions (entry 40).
propan-2-ol;isopropyl alcohol;isopropanol is subject to UK-REACH restrictions (entry 40).
n-butyl acetate is subject to UK-REACH restrictions (entry 40).
2-methylpropan-1-ol;iso-butanol is subject to UK-REACH restrictions (entry 40).
p-xylene;m-xylene;xylene;o-xylene is subject to UK-REACH restrictions (entry 40).

acetone;propan-2-one;propanone is subject to UK-REACH restrictions (entry 40).
4-hydroxy-4-methylpentan-2-one;diacetone alcohol is subject to UK-REACH restrictions (entry 40).

▼Additional information

Tactile warning.
If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources

The Management of Health and Safety at Work Regulations 1999.
The Health and Safety at Work etc. Act 1974 Regulations 2013.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
The Controlled Drugs (Drug Precursors) Regulations 2008.
Council Regulation (EC) No 2019/1148 on explosives precursors as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.
H225, Highly flammable liquid and vapour.
H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.
H361, Suspected of damaging fertility or the unborn child.
H373, May cause damage to organs through prolonged or repeated exposure.
H412, Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

▼Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

John Myland Ltd

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en