SAFETY DATA SHEET

High Build Friction Polish

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

High Build Friction Polish

▼Product no.

01-770-8093

Unique formula identifier (UFI)

GSH0-E18P-5N1M-53C1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Polish

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

John Myland Ltd.
26 Rothschild St,
Norwood
SE27 0HQ London
England
Tel: +44 (0) 208 670 9161
mylands.com

Contact person

Mylands

▼E-mail

info@mylands.com

Revision

05/09/2025

SDS Version

2.0

Date of previous version

02/05/2025 (1.0)

1.4. ▼Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.
Eye Irrit. 2; H319, Causes serious eye irritation.
STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)
Causes serious eye irritation. (H319)
May cause damage to organs through prolonged or repeated exposure. (H373)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

▼General

Not applicable.

Prevention

Do not breathe vapour/mist. (P260)
Wear eye protection. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
Get medical advice/attention if you feel unwell. (P314)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

▼Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

Does not contain any substances required to report

Additional labelling

UFI: GSH0-E18P-5N1M-53C1

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
ethanol;ethyl alcohol	CAS No.: 64-17-5 EC No.: 200-578-6 UK-REACH:	40-60%	Flam. Liq. 2, H225 Eye Irrit. 2, H319	

	Index No.: 603-002-00-5			
methanol	CAS No.: 67-56-1 EC No.: 200-659-6 UK-REACH: Index No.: 603-001-00-X	1-3%	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 (Central nervous system) (Oral, Inhalation)	[1], [3]
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	CAS No.: 64742-82-1 EC No.: 919-446-0 UK-REACH: Index No.:	1-3%	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT RE 1, H372 (Inhalation) Aquatic Chronic 2, H411	[15], [19]
butan-1-ol;n-butanol	CAS No.: 71-36-3 EC No.: 200-751-6 UK-REACH: Index No.: 603-004-00-6	1-3%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	
allyl alcohol	CAS No.: 107-18-6 EC No.: 203-470-7 UK-REACH: Index No.: 603-015-00-6	<1%	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 3, H331 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.
[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.
[15] The classification as a carcinogen / mutagen will not be taken into account as the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7) (CLP, Annex VI, note P).
[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: ●3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.
Use explosion-proof [electrical/lighting/ventilating] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Avoid direct contact with the product.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Take action to prevent static discharges.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

▼Storage conditions

No specific requirements.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼Control parameters

ethanol;ethyl alcohol
Long term exposure limit (8 hours) (ppm): 1000
Long term exposure limit (8 hours) (mg/m^3): 1920

methanol
Long term exposure limit (8 hours) (ppm): 200
Long term exposure limit (8 hours) (mg/m^3): 266
Short term exposure limit (15 minutes) (ppm): 250
Short term exposure limit (15 minutes) (mg/m^3): 333
Annotations:
Sk = Can be absorbed through the skin and lead to systemic toxicity.

butan-1-ol;n-butanol
Short term exposure limit (15 minutes) (ppm): 50
Short term exposure limit (15 minutes) (mg/m^3): 154

Annotations:
Sk = Can be absorbed through the skin and lead to systemic toxicity.

Dimethoxymethane
Long term exposure limit (8 hours) (ppm): 1000
Long term exposure limit (8 hours) (mg/m³): 3160
Short term exposure limit (15 minutes) (ppm): 1250
Short term exposure limit (15 minutes) (mg/m³): 3950

allyl alcohol
Long term exposure limit (8 hours) (ppm): 2
Long term exposure limit (8 hours) (mg/m³): 4,8
Short term exposure limit (15 minutes) (ppm): 4
Short term exposure limit (15 minutes) (mg/m³): 9,7
Annotations:
Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

allyl alcohol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	125 µg/kg bw/day
Short term – Systemic effects - Workers	Dermal	7.6 mg/kg bw/day
Long term – Systemic effects - Workers	Inhalation	4.63 mg/m³
Short term – Local effects - Workers	Inhalation	12.1 mg/m³
Short term – Systemic effects - Workers	Inhalation	12.1 mg/m³
Long term – Systemic effects - General population	Oral	75 µg/kg bw/day

butan-1-ol;n-butanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	3.125 mg/kg bw/day
Long term – Local effects - General population	Inhalation	155 mg/m³
Long term – Local effects - Workers	Inhalation	310 mg/m³
Long term – Systemic effects - General population	Inhalation	55.357 mg/m³
Long term – Systemic effects - General population	Oral	1.562 mg/kg bw/day

Dimethoxymethane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	18.1 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	17.9 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	31.5 mg/m³
Long term – Systemic effects - Workers	Inhalation	126.6 mg/m³
Long term – Systemic effects - General population	Oral	18.1 mg/kg bw/day

ethanol;ethyl alcohol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day

Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m³
Long term – Systemic effects - Workers	Inhalation	380 mg/m³
Short term – Local effects - General population	Inhalation	950 mg/m³
Short term – Local effects - Workers	Inhalation	1900 mg/m³
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m³
Long term – Local effects - Workers	Inhalation	837.5 mg/m³
Long term – Systemic effects - General population	Inhalation	410 µg/m³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m³
Short term – Local effects - General population	Inhalation	640 mg/m³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m³
Short term – Systemic effects - General population	Inhalation	1152 mg/m³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m³

methanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	20 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	4 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	20 mg/kg bw/day
Long term – Local effects - General population	Inhalation	26 mg/m³
Long term – Local effects - Workers	Inhalation	130 mg/m³
Long term – Systemic effects - General population	Inhalation	26 mg/m³
Long term – Systemic effects - Workers	Inhalation	130 mg/m³
Short term – Local effects - General population	Inhalation	26 mg/m³
Short term – Local effects - Workers	Inhalation	130 mg/m³
Short term – Systemic effects - General population	Inhalation	26 mg/m³
Short term – Systemic effects - Workers	Inhalation	130 mg/m³
Long term – Systemic effects - General population	Oral	4 mg/kg bw/day
Short term – Systemic effects - General population	Oral	4 mg/kg bw/day

▼ PNEC

allyl alcohol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.2 µg/L
Freshwater sediment		12.7 µg/kg
Intermittent release (freshwater)		3.2 µg/L
Marine water		320 ng/L
Marine water sediment		1.27 µg/kg
Predators		330 µg/kg

Sewage treatment plant		10 mg/L
Soil		3.68 µg/kg

butan-1-ol;n-butanol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		82 µg/L
Freshwater sediment		324 µg/kg
Intermittent release (freshwater)		2.25 mg/L
Marine water		8.2 µg/L
Marine water sediment		32.4 µg/kg
Sewage treatment plant		2.476 g/L
Soil		16.6 µg/kg

Dimethoxymethane

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		14.577 mg/L
Freshwater sediment		13.135 mg/kg
Marine water		1.477 mg/L
Sewage treatment plant		10 g/L
Soil		4.654 mg/kg

ethanol;ethyl alcohol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		960 µg/L
Freshwater sediment		3.6 mg/kg
Intermittent release (freshwater)		2.75 mg/L
Marine water		790 µg/L
Marine water sediment		2.9 mg/kg
Predators		380-720 mg/kg
Sewage treatment plant		580 mg/L
Soil		630 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Respirator with the following filter:	Organic vapour filter	Organic vapour filter	EN14387

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn	-	-	

▼Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,5	> 480	EN374-2, EN16523-13, EN388	

▼Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

No data available.

▼Odour / Odour threshold

Alcohol odor

pH

No data available.

Density (g/cm^3)

No data available.

Kinematic viscosity

No data available.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)
Does not apply to liquids.
Boiling point (°C)
No data available.
Vapour pressure
No data available.
Relative vapour density
No data available.
Decomposition temperature (°C)
No data available.
Data on fire and explosion hazards
Flash point (°C)
No data available.
Flammability (°C)
The material is ignitable.
Auto-ignition temperature (°C)
No data available.
Lower and upper explosion limit (% v/v)
No data available.
Solubility
Solubility in water
No data available.
n-octanol/water coefficient (LogKow)
No data available.
Solubility in fat (g/L)
No data available.
9.2. Other information
Oxidizing properties
No data available.
Other physical and chemical parameters
No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.
10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.
10.3. Possibility of hazardous reactions
None known.
10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.
10.6. Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law
Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation
Based on available data, the classification criteria are not met.

Serious eye damage/irritation
Causes serious eye irritation.

Respiratory sensitisation
Based on available data, the classification criteria are not met.

Skin sensitisation
Based on available data, the classification criteria are not met.

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
Based on available data, the classification criteria are not met.

STOT-repeated exposure
May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard
Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects
Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties
This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information
None known.

SECTION 12: Ecological information

12.1. Toxicity
Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability
Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential
Based on available data, the classification criteria are not met.

12.4. Mobility in soil
No data available.

12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties
This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

▼Waste treatment methods

Product is covered by the regulations on hazardous waste.
HP 3 - Flammable
HP 4 - Irritant (skin irritation and eye damage)
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group
** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
Hazchem Code: ●3YE

14.6. Special precautions for user
Not applicable.

14.7. Maritime transport in bulk according to IMO instruments
No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application
People under the age of 18 shall not be exposed to this product.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education
No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances
P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes
methanol

UK-REACH, Annex XVII
methanol is subject to restrictions, UK-REACH annex XVII (entry 69).
ethanol;ethyl alcohol is subject to UK-REACH restrictions (entry 40).
methanol is subject to UK-REACH restrictions (entry 40).
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) is subject to UK-REACH restrictions (entry 40).
butan-1-ol;n-butanol is subject to UK-REACH restrictions (entry 40).
Dimethoxymethane is subject to UK-REACH restrictions (entry 40).
allyl alcohol is subject to UK-REACH restrictions (entry 40).

Additional information
Tactile warning.

Sources
The Management of Health and Safety at Work Regulations 1999.
The Health and Safety at Work etc. Act 1974 Regulations 2013.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment
No

SECTION 16: Other information

▼Full text of H-phrases as mentioned in section 3
EUH066, Repeated exposure may cause skin dryness or cracking.
H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.
H301, Toxic if swallowed.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H311, Toxic in contact with skin.
H315, Causes skin irritation.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H331, Toxic if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.
H370, Causes damage to organs. (Central nervous system) (Oral, Inhalation)
H372, Causes damage to organs through prolonged or repeated exposure. (Inhalation)
H400, Very toxic to aquatic life.
H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

John Myland Ltd

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en