SAFETY DATA SHEET

Wax Liming

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
Wax Liming

Product no.
16-785-8012

Unique formula identifier (UFI)
70J6-QRSG-4KGE-XTVF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
Wax

Use descriptors (UK REACH)

Product category	Description
PC 31	Polishes and Wax Blends

Uses advised against
None known.

1.3. Details of the supplier of the safety data sheet

Company and address
John Myland Ltd.
26 Rothschild St,
Norwood
SE27 0HQ London
England
Tel: +44 (0) 208 670 9161
mylands.com

Contact person
Mylands

E-mail
info@mylands.com

Revision
18/08/2025

SDS Version
1.0

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Skin Irrit. 2; H315, Causes skin irritation.
Skin Sens. 1; H317, May cause an allergic skin reaction.
Eye Irrit. 2; H319, Causes serious eye irritation.
STOT SE 3; H336, May cause drowsiness or dizziness.
STOT RE 1; H372, Causes damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Flammable liquid and vapour. (H226)
May be fatal if swallowed and enters airways. (H304)
Causes skin irritation. (H315)
May cause an allergic skin reaction. (H317)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)
Causes damage to organs through prolonged or repeated exposure. (H372)
Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Do not breathe vapour/mist. (P260)
Do not eat, drink or smoke when using this product. (P270)

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
Get medical advice/attention if you feel unwell. (P314)

Storage

Store locked up. (P405)

Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
turpentine, oil

Additional labelling

UFI: 70J6-QRSG-4KGE-XTVF

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	CAS No.: 64742-82-1 EC No.: 919-446-0 UK-REACH: Index No.:	40-60%	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT RE 1, H372 (Inhalation) Aquatic Chronic 2, H411	[15], [19]
turpentine, oil	CAS No.: 8006-64-2 EC No.: 232-350-7 UK-REACH: Index No.: 650-002-00-6	10-15%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Aquatic Chronic 2, H411	[19]
Propylidynetrimethanol	CAS No.: 77-99-6 EC No.: 201-074-9 UK-REACH: Index No.:	<0.25%	Repr. 2, H361fd	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[15] The classification as a carcinogen / mutagen will not be taken into account as the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7) (CLP, Annex VI, note P).
[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.
Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.
Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: ●3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.
Use explosion-proof [electrical/lighting/ventilating] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Avoid direct contact with the product.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Take action to prevent static discharges.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

No specific requirements.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Paraffin Wax 58-60 DegC
Long term exposure limit (8 hours) (mg/m^3): 2
Short term exposure limit (15 minutes) (mg/m^3): 6

turpentine, oil
Long term exposure limit (8 hours) (ppm): 100
Long term exposure limit (8 hours) (mg/m^3): 566
Short term exposure limit (15 minutes) (ppm): 150
Short term exposure limit (15 minutes) (mg/m^3): 850

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Long term exposure limit (8 hours) (mg/m^3): 10(inhalable)/4(respirable)

Zirconium dioxide
Long term exposure limit (8 hours) (mg/m^3): 5 (As Zr)
Short term exposure limit (15 minutes) (mg/m^3): 10 (As Zr)

Aluminium hydroxide

Long term exposure limit (8 hours) (mg/m³): 2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Aluminium hydroxide

Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	10.76 mg/m³
Long term – Systemic effects - Workers	Inhalation	10.76 mg/m³
Long term – Systemic effects - General population	Oral	4.74 mg/kg bw/day

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m³
Long term – Local effects - Workers	Inhalation	837.5 mg/m³
Long term – Systemic effects - General population	Inhalation	410 µg/m³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m³
Short term – Local effects - General population	Inhalation	640 mg/m³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m³
Short term – Systemic effects - General population	Inhalation	1152 mg/m³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m³

Propylidynetrimethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	340 µg/kg bw/day
Long term – Systemic effects - Workers	Dermal	940 µg/kg bw/day
Long term – Systemic effects - General population	Inhalation	580 µg/m³
Long term – Systemic effects - Workers	Inhalation	3.3 mg/m³
Long term – Systemic effects - General population	Oral	340 µg/kg bw/day

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	28 µg/m³
Long term – Local effects - Workers	Inhalation	170 µg/m³

PNEC

No data available.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.
Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Respiratory protection is not needed in the event of adequate ventilation.			

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,5	> 480	EN374-2, EN16523-13, EN388	

Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Paste

Colour

White

Odour / Odour threshold

Perceptible odour

pH

No data available.

Density (g/cm^3)

No data available.

Kinematic viscosity

No data available.

Particle characteristics
No data available.

Phase changes

Melting point/Freezing point (°C)
No data available.

Softening point/range (°C)
No data available.

Boiling point (°C)
No data available.

Vapour pressure
No data available.

Relative vapour density
No data available.

Decomposition temperature (°C)
No data available.

Data on fire and explosion hazards

Flash point (°C)
No data available.

Flammability (°C)
The material is ignitable.

Auto-ignition temperature (°C)
No data available.

Lower and upper explosion limit (% v/v)
No data available.

Solubility

Solubility in water
No data available.

n-octanol/water coefficient (LogKow)
No data available.

Solubility in fat (g/L)
No data available.

9.2. Other information

Oxidizing properties
No data available.

Other physical and chemical parameters
No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.

10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions
None known.

10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] has been classified by IARC as a group 2B carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste.
HP 3 - Flammable
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 13 – Sensitising
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	III	Yes	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	III	Yes	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	III	Yes	See below for additional information.

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
						

* Packing group
** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
Hazchem Code: ●3Y

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes
E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

UK-REACH, Annex XVII

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) is subject to UK-REACH restrictions (entry 40).
turpentine, oil is subject to UK-REACH restrictions (entry 40).

Additional information

Tactile warning.
If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources

The Management of Health and Safety at Work Regulations 1999.
The Health and Safety at Work etc. Act 1974 Regulations 2013.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.
H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H336, May cause drowsiness or dizziness.
H361fd, Suspected of damaging fertility. Suspected of damaging the unborn child.
H372, Causes damage to organs through prolonged or repeated exposure. (Inhalation)
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

PC 31 = Polishes and Wax Blends

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average

UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

John Myland Ltd

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en